# Useful Reference Points • www.hae.org.uk/businessguard

Before Starting Work.

### **AAHA XHOW**

- conid distract you. safe and that no one is near to you or Make sure that the area is clear and 1
- parriers and signs around your work Warn others to keep away, place associated with working at height. Protect other people from the risk .S.
- authority may be required from the pedestrian areas, a permit or written In certain locations, such as public and 31
- services or ducts. inspected for hidden underground surfaces. Ensure that the ground is 4. Use with caution on uneven or sloping юся долегителт.
- trom other services. where possible isolate potential risks Keep away from electrical services and **'**G

## DISMANTLING MOBILE ACCESS PERONS USING/ASSEMBLING OR

- whenever using mobile access towers. minimum that should be worn protective equipment (ppe) are the 1. The following items of personal HAWOI
- footwear ideally safety boots to EN345. You must wear suitable protective
- Hard hat with chin strap to EU397. 31

VP Hire Station

v:012017

- will also need to wear appropriate Persons working near this equipment ·Þ
- personal protective equipment.

- The Crescent Birmingham Business Park noo sinegen uce vesociation ⊨urope
- **3YT TEB Iludilos**

-9

**'**G

31

·7

structure.

.menī

postds.

sssemble guide.

ni beitioeqa

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia

Mort has been made by haz-irna to ensure that the morthadon prefine this document as appointed in a second and not misleading. HAZ-IFAA cannot accept responsibility for any loss or liability percent ave arisen from the use of any such document/material. Only Acts of Parliament and Statutory Ins





1201 Safety Guidance

Important note: This document must be read in

conjunction with the original assembly guide

1. It is important to read this leaflet and the manufactures

system.

Gloves.

of drugs or alcohol.

mobile access tower.

each of the working platforms/Decks.

Prepare a risk assessment for the task.

Hard hat with chin strap to EN397

Boots or protective footwear to a minimum EN345

or permanent disability must seek expert advice before using it.

then you should make it secure to prevent unauthorised use

2.

3.

4

5.

6.

7.

8

10.

assembly guide before you use the mobile access tower

Do not exceed the maximum load of the mobile access

tower. This information is detailed on the castors of the

Do not exceed the Safe Working Load (SWL) detailed on

Mobile Access Towers

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

If you have not used assembled or dismantled a mobile access tower before

familiarise yourself with the equipment's components before you start the main task.

Plan your work and think ahead to make sure that you will always be working safely.

The mobile access tower must not be used by minors, or by anyone under the influence

This equipment is designed for use by an able bodied adult. Anyone with either temporary

If the mobile access tower is to remain in position when unattended, for example overnight,

You should have at least the following items of personal protective equipment:





























nuil all persons and equipment has

Do not move the mobile access tower

the side of a building or other rigid

the tower by pushing too hard against

on the platform, take care not to topple

When drilling or using other equipment

they will act like a sail if the wind catches

sheeting and tarpaulins on the tower:

outside if it is windy. Take care using

Do not use the mobile access tower

assembled to the heights specified for

The mobile tower must only be

plates and appropriate load bearing

castors should be replaced with base

rsed on soft or uneven ground,

suitable. Where the equipment may be

tower make sure the ground surface is

Before setting up the mobile access

number of components are used as

1. Ensure that the correct type and

MOBILE ACCESS TOWER SYSTEMS

the manufacturers

əuı

manufacturers assembly guide.

interior or exterior use in







1

## 44 (0) 121 380 4600 44 (0) 121 333 4109 e.org.uk

reverse of this leaflet.

aecks/plattorms.

uonisod

Jauddns

ed of

new location.

**GU SETTING UP** 

**CASTOR AND ADJUSTABLE LEGS** 

End Collar - Free from damage

Adjusters - Moves freely

Wheels - Move & Rotate

Brake - Check function

**OUTRIGGERS OR STABILISERS** 

Castings - Free from damage

Interlock Clips - Function

Welds - Free from cracks

Tubes - Straight & free from dents

Straightness

Spindle

Housing

Spigot

Foot

Nuts & Bolts

Clip function

Thread - Free from damage





using the simple check guide on the

when working from the equipment.

3. Ensure that where platforms have

circumstances must these

uo

are a mandatory requirement.

unged openings, these remain closed

removed. In most circumstances these

rails/hand rails and toe boards are in

methods. Seek advice from your

necessary for the mobile access tower

height of the tower and re-erect it at the

conditions, uneven ground or slight wind, it may be safer to reduce the

position while standing on the ground.

mobile access tower to its new

been removed. Push and pull the

1. Under certain conditions it may be

**USING THE MOBILE ACCESS TOWER** 

7. If moving the tower in adverse

2. Ensure that the required guard

nuger

all

"tied-in" using approved

Inspect the components before use

eik Fax: mail:



2450 Regents Court The Crescent

# oham Business Park olihull B37 7YE



©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

θG

working

Please keep this leaflet safely as it may be required for future reference

For guidance on managing

construction health risks go to www.hse.gov.uk/construction

•

.

•

•



Please keep it until you finish work .

You may want to read this leaflet again.

company or the insurer straight away.

insurance cover, check with the hire

unlikely that a normal insurance policy

плоичед пл а підпичау ассіделт, іт із

pelonging to a third party, or if you are

you cause any damage to property

equipment yourself against theft or

4. In addition, you should be aware that if

3. However, you must always secure the

2. Some hire companies will offer

unreasonable damage such

equipment. You must indemnify the

responsible for the safe custody of the

1. Under the terms of hire, you are

isuiebe

company

SP

oL SSOL

insurance cover at an extra cost.

2. If you are in doubt about your

will give you any protection.

vandalism.

vandalism.

nre

**JONAHUZNI** 

Welds - Free from cracks Deck fixing rivets Deck damage • Hinges – Function

## DECKS/PLATFORMS

Labels - States SWL

**TOE BOARDS AND CLIPS** 

Timber – Straight

Fittings - Function

Hooks –Function freely

Reinforcements

**FRAMES & LADDERS** 

· Rungs - Free from damage

Weld - Free from cracks

Uprights/tubes - Straight

Clip-in guard rail/Hand rail frames

Ladder/Stiles/Rungs – Free from

Castings – No cracks

.

damage

Spigots

- **Supports**