

Before Starting Work.

TNIA9 DABN

- 1
- If stripping paint off an old building, the bottom layers of paint may contain lead.

- **.**2
- Lead paint should not be burnt off: it Wear a facemask. 3
- °t
- It is possible to very carefully warm the lead paint up to soften it without burning it. It can then be scraped off and disposed of carefully.
- OQ **'**G
- Do not allow the scraped paint anywhere near the mouth. Do not let officers touch it. Dispose of it sensibly Hands must always be washed atter handling lead paint.
- **WORK AREA**
- Do not use this hot air gun where there is a danger of explosion. It will ignite funnes from petrol, or gas exilindere - 1

VP Hire Statio

v:032017

- **.**2 ·suapunk:
- Make support of the stream is clear and Make support of the stream is clear and could cause a distraction. Protect others from the noise and danger. Warn others to keep away. 3
- ·t
- Do not use this hot air gun in the rain or where it may get wet.
- **SHOTAREGO**
- The following items of personal protective equipment (ppe) are the minimum finat should be worm when using this machine. Particular jobs or environments may require a higher level of protection.
- When removing paint or doing work that creates tunes an appropriate race mask must be worn with a minimum of EN149 FFP3(s) **.**2
- orotection.
- səlbbon unow od isum 31
- working with this hot air gun (EN166 or BS2092).
- ·•

- This equipment is likely to cause noise levels up to 101 dB(A) appropriate ear muffs or plugs giving

- Association Europe

3YT TEB Iludilos

The Crescent Birmingham Business Park :lism3 nuou sinegen uce

'9

·ŧ

3

'Z'

1

.9

'G

NUD AIA TOH

:euoudeie

effort has been made by HAE/EHA to ensure that the information given in this docun

plastic.

Contact the hire company. Contact the hire company. The company on the machine astrones the supply. Connections abould not be forced or improvised. Machines with a cyclindrical yellow industrial plug fitted are designed to function the supplied take portable transformer if the machine inte company will have provided a fitte connection take transformer has been supplied, take transformer has been supplied, take transformer has been supplied, take transformer noving it about – it may be heavier than it appears. Machines designed to run directly from a 230v mains will have either a normal square pin plug fitted, or a normal square pin plug fitted, or a hole industrial plug.

Check the machine, cables and plugs. If anything is found to be adamaged, do not use the hot air gun. Contact the hire company.

If using the hot air gun to remove any types of paint or variath, handa must always be washed after completing, the work, especially before smoking, eating or drinking.

Anybody who is working nearby will also need to wear appropriate personal protective equipment.

hearing protection for this level must be worn as a minimum.

- Dide indexina prod. Removing paint and varnish with a hot air gun will produce toxic tumes. A face mask must be wonn keep others away from the tumes. Be careful where the hot air is directed. It will crack glass and melt animals. It will crack glass and melt plastic.





0904 Safety Guidance

It is important to read this entire leaflet

BEFORE using the Hot Air Gun

Electricity is dangerous and must always be used with

Removing paint, especially lead paint, is hazardous. Wear a facemask. Do not allow others to breathe the fumes.

This hot air gun is designed for paint stripping, moulding

special plastics, thawing frozen water pipes and similar

The action of this hot air gun can cause injury if not used

Ear muffs or plugs giving protection for levels up to 101 dB(A);

Facemask – a minimum of EN149 FFP3(s) protection;

in a careful and controlled way.

Goggles : EN166 or BS2092;

Rcd if using a 230v (mains) supply.

Hot Air Gun

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

If the operator has not used a hot air gun before, they should familiarise themselves with the machine on some straightforward work before starting the

The work should be thought out and planned ahead to ensure that it is carried

The following items of personal protective equipment must be worn as a minimum:

This machine must not be used by minors, or by anyone under the influence of

This hot air gun is designed for operation by an able-bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.

ty enotinable been made by here ten to ensure unat the mormation given in this document and sopporting the is accurate and not misleading. HAE/ENA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments

have the force of law and only the courts can authoritatively interpret the law.

For guidance on managing

construction health risks go to www.hse.gov.uk/construction

Using the Hot Air Gun

Removing paint and varnish with a hot air gun will produce toxic fumes. Wear a

Do not direct hot air on to glass it will crack. Some plastics will crack and splinter

Remember material that has been worked on will remain hot for some time. Make

Switch off the hot air gun and unplug before making any adjustments. Remember the

Switch off and remove the plug then put the machine down in a safe place to cool

unplug at the mains before inspecting it. If the cable attached to the hot air gun

is damaged, stop using the machine. Contact the hire company. If an extension

10. If it is suspected that the cable may be cut or damaged in any way, switch off and

11. If the equipment does not work properly do not attempt to repair it. Contact the

Please keep this leaflet safely as it may be required for future reference

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

5. Make

·Þ

31

.2

0 TER 5

Wear the protective equipment including ear defenders and goggles.

Do no point the hot air gun at people. It will cause burns.

Take care not to accidentally pull the plug from the socket.

facemask, keep others away from the fumes.

1.

2.

3

4.

5.

6.

7

8.

9.

before melting.

nozzle will be hot.

hire company.

sure no-one touches it.

before leaving unattended.

Keep the cable out of the way.

cable has been damaged do not use it again.

Hiro Association Euro

2450 Regents Court

Birmingham Bus Bolihull B37 7YE

The C

Into the rect. The extension cable should be laid out carefully avoiding liquids, sharp edges, doorways or windows where affould be unrolled fully or it will should be unrolled fully or it will should be unrolled fully or it will should be unrolled fully overheat and could catch fire. or windows and could catch fire. The stension cable connections are dry and safe.

The extension caple is needed, instructions supplied with it. If an extension caple is needed, follow any special instructions given have not given any resed. Flug it directly into the rcd.

Use the 'TEST' button to check that the rod is working each time it is used. Reset the rod according to the isothistican supplied with it

VOM BLOE FLOGY Use a residual current device (rcd) plugged directly into the 230 volt ascriet. Plug the socket. Plug the protect against protect against electric shock if the

Provide the transformer of the transformer of the extension cable should be laid out carretully avoiding liquids, sharp edges, doorways or windows where vehicles might run over it. It will be tuly unrolled or it will should be turbed by the turbed by the turbed by the turbed by turbed by

should be used, not longer than 50 meters (160 feet). The extension meters (160 must only be used between the transformer and the machine.

protect against electric shock if the cable or machine get damaged.

ыи ов вгле ргле)

1.

2.

3.

5.

6.

8.

9

121 380 4600

e.org.uk

44 (0) 121 333 4109

www.hae.org.uk

has not given any special instructions, only a suitably rated heavy duty 110v extension cable

it an extension cable is needed, follow any instructions given by the nee company. If the hire company base not given any special short or the second second second parts in the second second

into the 230 volt cont socket. Do not use any 230 volt extension cables.

PLUG) 110 VOLT EQUIPMENT (YELLOW Read the instructions below for the machine being used.

230v machines will have either a normal square pin plug fitted, or a blue industrial

The machine will only operate on one voltage: it will be 110v or 230v. 110v machines will have a yellow industrial plug fitted.

10. Check on how the on/off switch operates – before switching the hot all gun on it must be known how to stop it.

Do not use the hot air gun to dry clothes or hair.

Keep the cable away from heat. After use the nozale will be hot. Do not touch it or lay it down on filammable material. Do not leave the hot air gun switched on when stoping work and lay it down even if it is only for a short while. Do not use the hot air gun to dry while.

If using a portable transformer, plug the transformer directly into the 230 volt

YTERCAL SAFETY

.2

1

.6nid

6

.8

-0

great care.

tasks.

main task.

out safely.

Gloves:

drugs or alcohol.





