Using the Chainsaw

- Wear ALL of he chainsaw protective equipment.
- Make sure that you have a firm footing, and there is no danger of slipping or stumbling while working.
- Make sure that the tip of the guide bar does not accidentally touch anything. If it does, the saw may kick back and cause an injury.
- Stop the saw before putting it down, or carrying it anywhere. Put the guide bar cover back on.
- Always keep left hand on the front handle, with right hand on the rear handle, controlling the throttle. Stop the saw if timber requires moving.
- If the saw throws out sawdust instead of chippings, it is a sign that the chain is becoming blunt. Stop the saw, and change the chain, adjusting the tension to suit.
- You should always be alert when using the chainsaw. If you are tired, leave the job
- Stop the engine if leaving the machine unattended.
- Put the guide bar cover back on when work is finished.
- 10. If the equipment does not work properly, do not attempt to repair it. Contact the hire company.
- 11. You may want to read this leaflet again. Please keep it until you finish work

Please keep this leaflet as it may be required for future reference







2450 Regents Court

The Crescent









44 (0) 121 333 4109

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

Place the chainsaw squarely on its base plat on the ground. Make sure that the chain is no to the ground or any obstruction. If the chain saw has a decompression valve, set it. You need to set the decompression valve each time a fresh attempt is made to start the engine.

Set the choke lever to $\overline{\Delta}$ if the engine is cold. If the engine is warm, the choke control should be in the running position $\overline{\overline{\Delta}}$.

Now release the throttle, control lever, and interlock: the throttle is now in position ready to start.

Press the interlock and the throttle at the same time. Whilst keeping these pressed in, pull the control lever back to the starting position [al.]

This is a brief description of the controls found on most chain saws. Check the saw to find the controls before trying to start it.

STARTING FROM COLD

The choke control should only be used when first attempting to start the engine from cold Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.

The machine may have a decompression valve. This is only used when starting the chainsaw it needs to be pressed before each fresh attempt to start the engine.

when starting the engine. noitison **I** that it is at the **D** position. To the both of the sand to the control lever forward to the sand the sand the rest position | ✓ I was a supplied that sand the control of th The main control lever has three

trigger, to prevent the throttle being squeezed to or pressed accidentally. You always need to press the interlock in before you can squeeze the interlock in before you can squeeze the throttle There is an interlock control on the throttle

This is a brief description of the controls found on most chain saws. Check the saw to find the controls before trying to start it.

CONTROLS STARTING THE CHAINSAW

12. Check the level of chain oil.

11. Put all tuel cape back on properly, and move fuel can to a safe, cool place.

- 10. If you spill any fuel on your clothes, change them straight away. If you spill any fuel on the ground, wipe if up or cover it with soil. Vipe any fuel off the machine. Dispose of fuel paked cloth carefully.
- Use a funnel when refuelling. Do not spill any fuel on yourself or the machine.
- Shake the fuel can to mix the petrol and oil. Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.
- It possible, move the machine away from work
- Stop the engine and let it cool down. e oil to 25 measures of petrol (40 ml per
- with petrol. If the hire company have given special instructions on how much oil to use, follow them. Otherwise use 1 measure of two follow them: mixture of two stroke engine oil Use a fresh .r No smoking.

REFUELLING

Make sure that the control switch is off before checking the chain tension. Wear chainsaw mitte ave nails or other toreign bodies in it.

Do not use the saw for cutting timber that may Check that the chain oil tank is topped up before starting work.

nave nalis or other toreign bodies in it. Do not use the saw for cutting timber that may

trees without solid wood. Do not use the saw for cutting small shrubs or Do not use the saw for any work that requires the user to be off the ground, for earnyle standing on a ladder or a platform, or any work involving cutting above shoulder height.

or hung-up trees. Get a professional tree surgeon to do these jobs.













Chainsaw

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read all of this leaflet **BEFORE** you use the Chainsaw

- Plan your work and think ahead to make sure you will always be
- This chainsaw is a powerful cutting tool which can cause very serious injuries if not used properly. You must be fully competent to use it. Do not allow anyone else who is not fully competent to use it.
- Great care must be taken at all time when working with the saw. If in any doubt about how to use the saw, do not use it.
- Work with trees and timber can be hazardous if you are in any doubt about your competence to do the job in hand, do not do it. Get a trained, competent professional to do the work, or find an alternative method which you are competent to handle.
- Petrol is highly flammable. Take care not to cause a fire or explosion.
- This chainsaw is designed for felling and trimming timber. Do not use it for anything else.
- You should wear as a minimum, the following personal protective equipment: Face shield or chainsaw mesh visor:

Ear defenders; Chainsaw safety mitts

Chainsaw leg protectors giving all-round leg protection;

Chainsaw protective gait

Industrial steel toe-cap boots.
Chainsaw protective boots can be worn in lieu of safety boots and gaiters.

Chainsaws must not be used by minors, or by anyone under the influence of drugs or

- Chainsaws are designed for use by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using them.













is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perc have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Ins to have arisen from the use of any such document/material. Only Acts of Parliament and Statu.

have the force of law and only the courts can authoritatively interpret the law.

> 44 (0) 121 333 4109 44 (0) 121 380 4600

a fully competent professional operator. In the study to cut down any ties over 4 metres in height or with a trunk greater than 150mm diameter. Do not fit to cut up any ties nesses when standing. Do not study the standing to the study of t

ck the chain brake by pushing the froi d guard forward. You should not be able f e the chain

The chain should move easily, around the guidebar, without being loose.

Check the chainsaw, engine, chain, and all equipment. Do not use anything found damaged - contact the hire company.

Anybody who is working near to you will also need to wear appropriate personal protective

gaiters. Chainsaw protective boots can be worn instead of safety boots and gaiters.

Wear chainsaw leg protectors giving all-round leg protection and chainsaw protective

A safety helmet must be worn when working with this machine. Tie up any long hair to prevent it getting caught in the machine.

This equipment is likely to cause noise levels up to 85 dB(A) - wear Ear defenders giving

A face shield or chainsaw mesh visor must be

worn when working with this machine

aring protection for this level as a minimum.

wear industrial steel toe-cap safety boots.

Protect hands with chainsaw safety mitts.

sure that the control switch is off before king the chains wear chain tension. Wear chainsaw

CHAINSAWS

The Crescent Birmingham Business Park noo sinegen uch



2. The following items of personal protective competence to use the saw.

BAY 788 Iludilos

If you are using the chainsaw 'at work', you must be trained and competent. You may for any work with trees. You must not allow for any work with trees. You must not allow the snyone who does not have the required competence to use the saw.

SHOTARIANO

Make sure that the timber you are going to cut will not move. Use a proper 'horse' when cutting smaller pieces of wood.

Protect other people from the noise and from danger. Warn others to keep away, put up warning signs or barriers around your work areas.

Make sure that the area is clear and safe are that no-one is near to you or could distra

Using this equipment indors or in confined bear continued aborses could cause affait school bearses consider the transfer continued and only use it in other indoor situations if its suit ability and the variation required has bear a variability and the suit of the continued of the continued on the continued of the continued of

Do not use this chainsaw where there is danger of explosion, It will ignite furnes troperol, or gas cylinders.

MORK AREA

What to do it the chain becomes blunt. How to avoid blunting the chain. How to start, and stop, the saw.

How to stand correctly when using the saw and what the correct cutting action is.

How the chain brake works and what it does

What 'kick back' is and what cutting actions lead to 'kick back'. The hazardous areas on the saw.

The location, and function of all the controls.

You must be competent to use this chainsaw. Before stating work, check that, you fully understand, do not use it sanything you do not understand, do not use the saw. Check with your employer, or the hire company.

COMPETENT OPERATOR





