



Redistributed under licence from HAE by Hire Station. Licence expires on 01/02/2020

Using the Floor Grinder

- All protective equipment must be worn including ear defenders and goggles.
- The floor grinder must always be gripped correctly with two hands while working.
- The machine must be running at full speed before lowering the abrasives carefully onto the surface.
- When grinding or scouring, the grinder must be moved over the floor in a circular scything motion. If using wire brushes the machine should be pulled backwards, taking care not to trip. This will avoid compacting the loosened surface debris by not walking over it.
- Care must be taken not to damage any finished floor surfaces by operating the machine while moving to the work area and positioning the floor grinder.
- If the machine starts to labour, reduce the depth of cut and make two passes.
- While working, a lookout must be kept for any obstructions on the path of the grinder, stop the grinder and clear them out of the way.
- As the abrasives wear the tilting handle must be adjusted to maintain a level contact between the abrasives and floor.
- Do not adjust the tilting handle in an effort to increase the pressure onto the floor. This will not do the job faster but will wear out the abrasive attachments much quicker.
- Periodically check, and tighten the wedges as necessary.
- The engine must be stopped if the abrasive attachments need to be changed or adjustments need to be made.
- Watch out for signs that vibration may be affecting the hands. If the fingers begin to tingle or feel numb a short break must be taken from the work. The fingers must be exercised to encourage blood circulation.
- To help prevent vibration affecting the hands, the machine should be operated for shorter periods. Hands should be kept warm – gloves can be worn to help do this.
- Stop the engine if leaving the machine unattended.
- If the equipment does not work properly, do not attempt to repair it. Contact the hire company.

Please keep this leaflet safely as it may be required for future reference



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

1. The drive unit should be held firmly so that it will not move when the starter is pulled. The starter cord should be pulled slowly until it is apparent that the starter has engaged with the engine, it should then be pulled quickly and strongly. It should not be pulled too far or it may break. The cord should be guided back into place so that it recoils correctly.

2. If the engine has started adjust the throttle to stop the engine, the throttle lever should be closed, and the fuel tap should be turned off.

3. The fuel tap should be turned on.

4. The fuel tap should be checked.

5. The fuel and oil levels should be checked. Instructions below.

6. If the hire company has given special instructions, follow them, if not follow the instructions below.

7. The fuel and oil levels should be checked.

8. Do not use any other wedge except those hardwood wedges supplied by the hire company.

9. Lift the handle to stand the machine upright.

10. Rotate the tilting handle to adjust the machine to ensure the abrasives are resting evenly on the floor. The machine is now ready.

11. Whilst the work is being carried out, the wedges may gradually become loose. The machine should be periodically stopped and checked, and the wedges tightened as necessary.

1. Check the machine, engine, and all attachments must be used for the machine and for the job by the hire company.

2. Only the correct type of abrasive attachments must be used for the machine and for the job by the hire company.

3. Vibration from using this floor grinder can be hazardous. Hands must be warmed up before starting the work and gloves must be worn to keep the hands warm whilst working.

4. All of the controls must be understood. Before the machine is started it must be known how to top it.

5. The following items of personal protective equipment (PPE) are the minimum that should be worn whenever the machine is used. Particular jobs or environments may require a higher level of protection.

6. This equipment is likely to cause noise levels up to 102dB(A)-appropriate ear muffs or plugs must be worn giving hearing protection for this level as a minimum.

7. Impact resistant goggles must be worn (EN166-B or BS2092 grade 1) when this floor grinder is being operated.

8. An appropriate dust mask must be worn (with a minimum of EN149 FFP3(S) protection) when material is being planned that may cause dust.

9. Safety boots must be worn (EN345 or BS1870/4972).

1. Do not use this machine where there is a danger of explosion. It will ignite fumes from petrol, or gas cylinders.

2. Using this equipment indoors or in confined spaces could cause fatal carbon monoxide poisoning. Never use it in other indoor situations if its suitability and the ventilation required has been fully assessed. Mechanical extraction ventilation must be used in these situations.

3. Make sure that the area is clear and safe and that no-one is nearby and there are no distractions.

4. Protect people from the noise, debris and dust. Warn people to keep away, put barriers around the work area.

5. If the machine has a vacuum dust collection system then the machine should be operated with a dry surface. The dust collection will be more efficient.

6. If there is no dust collection system then damping down the surface to be worked on will help control dust.

7. The machine may damage pipes or cables laid just beneath the surface.

8. The following items of personal protective equipment (PPE) are the minimum that should be worn whenever the machine is used. Particular jobs or environments may require a higher level of protection.

9. This equipment is likely to cause noise levels up to 102dB(A)-appropriate ear muffs or plugs must be worn giving hearing protection for this level as a minimum.

10. Impact resistant goggles must be worn (EN166-B or BS2092 grade 1) when this floor grinder is being operated.

11. An appropriate dust mask must be worn (with a minimum of EN149 FFP3(S) protection) when material is being planned that may cause dust.

12. Safety boots must be worn (EN345 or BS1870/4972).

Useful Reference Points • www.hae.org.uk/businessguard

Floor Grinder

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read all of this leaflet BEFORE using the Floor Grinder



- Petrol is highly flammable. Take care not to cause a fire or explosion.
- This floor grinder is designed for grinding concrete surfaces, removing loose surface material or ridges, preparing the surface for painting; it can also be used for removal of dry grease or paint. The appropriate attachments must be used.
- The action of this floor grinder can cause injury or damage if the machine is not used in a careful and controlled way.
- If the operator has not used a floor grinder before, they should familiarise themselves with the machine on some straightforward work before starting on the main task.
- The work must be planned and thought out to ensure it will always be carried out safely.
- The following items of personal protective equipment must be worn as a minimum:
Impact resistant goggles: EN166 – B or BS2092 grade 1;
Dust mask – a minimum of EN149FFP3(s) protection;
Ear muffs or plugs giving protection for levels up to 102 dB(A);
Safety boots to EN345 or BS1870/4972;
Overalls and gloves.
- This machine must not be used by minors, or anyone under the influence of drugs or alcohol.
- This floor grinder is designed for operation by an able-bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE

1. Check the machine, engine, and all attachments must be used for the machine and for the job by the hire company.

2. Only the correct type of abrasive attachments must be used for the machine and for the job by the hire company.

3. Vibration from using this floor grinder can be hazardous. Hands must be warmed up before starting the work and gloves must be worn to keep the hands warm whilst working.

4. All of the controls must be understood. Before the machine is started it must be known how to top it.

5. The following items of personal protective equipment (PPE) are the minimum that should be worn whenever the machine is used. Particular jobs or environments may require a higher level of protection.

6. This equipment is likely to cause noise levels up to 102dB(A)-appropriate ear muffs or plugs must be worn giving hearing protection for this level as a minimum.

7. Impact resistant goggles must be worn (EN166-B or BS2092 grade 1) when this floor grinder is being operated.

8. An appropriate dust mask must be worn (with a minimum of EN149 FFP3(S) protection) when material is being planned that may cause dust.

9. Safety boots must be worn (EN345 or BS1870/4972).



WORK AREA
1. Do not use this machine where there is a danger of explosion. It will ignite fumes from petrol, or gas cylinders.

Useful Reference Points • www.hae.org.uk/businessguard